

RMS Max Energy Alkaline Battery



RMS-AAA	Packed 720 To a Master Carton, 40 to a Sub Carton
RMS-AA	Packed 720 To a Master Carton, 40 to a Sub Carton
RMS-C	Packed 192 To a Master Carton, 12 to a Sub Carton
RMS-D	Packed 144 To a Master Carton, 12 to a Sub Carton
RMS-9Volt	Packed 200 To a Master Carton, 10 to a Sub Carton
RMS-12Volt	Packed 50 To a Box

RMS Communications Inc

11516 Downs Road, Pineville, North Carolina. 28134 USA

Phone (704) 588-4008

www.rmscommunications.net Email: sales@rmscommunications.net

RMS Max Energy Battery

Technical Data & Packing:

- Description: Size AA, LR6, AM-3 Alkaline (Zn-MnO₂) Battery
- Nominal Voltage:1.5V
- Diameter: 13.5-14.5mm
- Height:49.2-50.5mm
- Shelf Life: 5 years
- Packing:
4 pcs/shrink; 60doz/carton; G.W.:18.0kgs; Carton size:31.0x19.0x17.5cm

Test Condition	Cut-off	Duration
10Ω 24h/d	0.9V	19.5h
1.8Ω 15s/min, 24h/d	0.9V	640cycle
3.9Ω 1h/d	0.8V	7.2h
10Ω 1h/d	0.9V	19.5h
43Ω 4h/d	0.9V	92.5h

Description: Size AAA, LR03, AM-4 Alkaline (Zn-MnO₂) Battery

- Nominal Voltage:1.5V
- Diameter: 9.5-10.5mm
- Height:43.3-44.5mm
- Shelf Life: 5 years
- Packing:
20 pcs/shrink;600pcs/carton; G.W.:7.5kgs; Carton size:25x19x10cm

Test Condition	Cut-off	Duration
20Ω 24h/d	0.9V	18.3h
3.6Ω 15s/min, 24h/d	0.9V	630cycle
5.1Ω 4min/h, 8h/d	0.8V	230min
10Ω 1h/d	0.9V	495min
75Ω 4h/d	0.9V	72.5h

RMS Communications Inc

11516 Downs Road, Pineville, North Carolina. 28134 USA

Phone (704) 588-4008

www.rmscommunications.net Email: sales@rmscommunications.net

RMS Max Energy Battery

Description: Size C, LR14, AM-2 Alkaline (Zn-MnO₂) Battery

- Nominal Voltage:1.5V
- Diameter: 24.9-26.2mm
- Height: 48.6-50.5mm
- Shelf Life: 5 years
- Packing:
2 pcs/shrink wrap; 8doz/carton; G.W.:8.0kgs; Carton size:30.5x20x12.0cm

Test Condition	Cut-off	Duration
3.9Ω 24h/d	0.9V	18.0h
3.9Ω 4min/h, 8h/d	0.9V	19.0h
3.9Ω 1h/d	0.8V	22h
6.8Ω 1h/d	0.9V	36h
20Ω 4h/d	0.9V	118h

Description: Size D, LR20, AM-1 Alkaline (Zn-MnO₂) Battery

- Nominal Voltage:1.5V
- Diameter: 32.3-34.2mm
- Height:59.5-61.5mm
- Shelf Life: 5 years
- Packing:
2 pcs/shrink; 12doz/carton; G.W.:20.7kgs; Carton size:32.0x28.2x15.0cm

Test Condition	Cut-off	Duration
2.2Ω 24h/d	0.9V	20.2h
2.2Ω 4min/h, 8h/d	0.9V	22.5h
2.2Ω 1h/d	0.8V	23.5h
3.9Ω 1h/d	0.9V	39.5h
10Ω 4h/d	0.9V	122h

RMS Communications Inc

11516 Downs Road, Pineville, North Carolina. 28134 USA

Phone (704) 588-4008

www.rmscommunications.net Email: sales@rmscommunications.net

RMS Max Energy Battery

Description: Size 9V, 6LR61Alkaline (Zn-MnO₂) Battery

- Nominal Voltage:9V
- Diameter: 26.5mm(L)x17.5mm(W)X48.5mm(H)
Shelf Life: 5 years
- Packing:
1 pcs/shrink; 200pcs/carton; G.W.:14.0kgs; Carton size:29.0x19.5x12.0cm

Test Condition	Cut-off	Duration
35mA 24h/d	5.4V	14.5h
180Ω 30min/d	4.8V	13.0h
270Ω 1h/d	5.4V	18.5h
620Ω 1h/d	5.6V	46h

RMS Communications Inc

11516 Downs Road, Pineville, North Carolina. 28134 USA

Phone (704) 588-4008

www.rmscommunications.net Email: sales@rmscommunications.net